

Excavators «HYDRAMET» for tractors



Excavator is indispensable not only during loading and unloading, but also in construction, earthworks.

The functionality of the excavator from HYDRAMET is expanded thanks to a large selection of working tools - buckets of various types, grips for wood, buckets for reclamation and beyond. The ideal option is to combine with a front loader. Large boom reach, depth of digging and affordable price.



The excavator is designed to work with tractors of class at least 1.4 for connection to the tractor, the capacity of the tractor hydraulic pump is 40 l/min is required, in case of lower capacity of the hydraulic system, an additional hydraulic pump with a drive from the power takeoff shaft must be used.

	Technical characteristics			
	H-500	H-300	H-500T	H-800T
Maximum height, mm	5622	2270	6163	7395
Depth of bucket digging, mm	1928	1500	2624	3149
Maximum coverage width (left, right), mm	3417	1700	3417	4101
Maximum useful coverage (forward), mm	4399	2880	5068	6081
Aggregation on tractors, kW	for tractors with 4 cylinders and minimum engine power from 80-100 h.p	for tractors with engine power from 40 h.p	for tractors with 4 cylinders and minimum engine power from 80-100 h.p	for tractors with 6 cylinders and minimum engine power from 120 h.p
Weight, kg	590	330	635	1040